

Pneumatic & Wheel Lockouts

Our pneumatic and wheel lockouts offer easy-to-use, innovative ways to lock out virtually any pneumatic fitting or steering wheels.

Pneumatic Lockout

Prevents pneumatic fitting from being connected to pressurized air source

- Fits virtually all male pneumatic fittings found in manufacturing facilities
- Stainless steel construction for corrosion resistance
- Measures 1-3/8" wide x 7-3/4" tall x 1/8" thick
- Accepts any Master Lock or American Lock Safety Padlock
- Works with lockout hasps for multiple worker lockout
- Patent Pending

	Patent Pending			100	3	
	Master Lock Model #	Description	D		Phi.	
	S3900	Stainless Steel Pneumatic Lockout			19	
(

Steering Wheel Covers

Provides Visual Deterrant for Vehicle Maintenance

- Three sizes available for various diameter steering wheels 16", 20", 24"
- Trilingual warning notifies employees not to start or move vehicle
- Lock in place with a 421 hasp and safety padlock
- For added security, use Safety Series 8611 or S806 lockout cables around steering wheel and foot pedals

Master Lock Model #	Description
4716	16" Diameter Steering Wheel Cover
4720	20" Diameter Steering Wheel Cover
4724	24" Diameter Steering Wheel Cover







S3900

