

PIG® HazMat Spill Kit in Bucket

#64CRSC - Absorbs up to 5 gal. • No Wheels • UN1H2/Y30/S



Grab-and-go response kit for up to 5 gallons can be wall-mounted to maximize visibility.

- Polyethylene bucket with easy-open, screw-on lid can be used to ship or temporarily store used absorbents
- PIG HazMat Socks stop spreading spills; PIG HazMat Pads absorb quickly
- PIG HazMat Absorbents are specially treated for unsurpassed performance with concentrated corrosives, such as 98% sulfuric acid and 30% sodium hydroxide
- Prepacked container provides easy access to contents
- Large, color-coded label makes identification fast and accurate
- Tamperproof seals help prevent pilfering of spill response supplies
- UN Rating 1H2/Y30/S for Packing Groups II and III
- Use as refill for wall-mount holder (sold separately)
- Only PIG Spill Kits feature PIG Absorbents proven for rapid response



64CRSC Specifications

Color:	White/Pink
Fluids Absorbed:	Acids, Bases & Unknowns
Absorbency:	Up to 5 gal.
Spill Volume:	1 - 9 gal.
Lift-out Basket:	No
Outdoor Storage:	No
UN Rated:	Yes
UV Resistant:	No
Wheels:	No
Sold as:	1 each
Weight:	11 lbs.
National Stock Number (NSN):	4235-01-431-4430
# per Pallet:	36
Composition:	Socks, Mats - 100% Polypropylene; Bucket - Polyethylene
Includes:	1 - 46" PIG® HAZ-MAT Sock (124CR) 1 - 10' PIG® HAZ-MAT Sock (PIG301) 4 - PIG® HAZ-MAT Pads (MAT310) 6 - Tamper-proof Labels (LBL100)

64CRSC Metric Equivalent

Absorbency:	Up to 18.9 L
Weight:	5 kg

Technical Information

Warnings & Restrictions:

HAZ-MAT Notice
To ensure effectiveness and your safety, we recommend that you conduct compatibility and absorption testing of your chemicals with PIG® HAZ-MAT products prior to purchase. If you have any questions or need samples to test, please call Technical Services.

Certifications, Approvals and Ratings:

UN1H2/Y30/S

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping.

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.120(j)(1)(vii) - OSHA's HAZWOPER standard requires spill responders to have, "DOT specified salvage drums or containers and suitable quantities of proper absorbents," in areas where spills may occur.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Material Safety Data Sheet (MSDS)

Chemical Compatibility (CCG)

