



TECHNICAL DATA SHEET

Regulatory Approval/Code Reference:

OSHA 29 CFR 1910.106(e)(2)(ii)(b):	Incidental storage or use of flammable and combustible liquids.
OSHA 29 CFR 1910.106(d)(3)(i&ii):	Design, construction, and capacity of storage cabinets - (i) Maximum capacity
International Fire Code	3404.3.2 - Liquid storage cabinets, 3404.3.2.1.1- Material , 3404.3.2.1.2 - Labeling, 3404.3.2.1.3 - Doors, 3404.3.2.1.4 Bottom
NFPA 1, The Uniform Fire Code –2006 Edition	60.1.2.23 Hazardous Materials Storage Cabinets
NFPA Code 30 – 2008 Edition	Chapter 9
The National Fire Code of Canada (NFC) 1995 Edition	Section 4.2.10.5 references storage cabinets must conform to ULC-C1275 ULC/ORD-C1275-84
FM Global	NOT APPROVED

Capacity:	55 GAL. (200 L) Horizontal Drum Cabinet
Exterior Dimensions (H x W x D):	50.25 x 30.00 x 48.00 (1276 mm x 762 mm x 1219 mm)
Interior Dimensions (H x W x D):	46.00 x 26.88 x 44.88 (1168 mm x 683 mm x 1140 mm)
Door Opening Dimensions (H x W):	44.00 x 26.00 (965 mm x 991 mm)
Material Specifications:	Cabinet architecture is 18ga steel thought, with fully welded construction. 2" leak tight sump, continuous door hinge Galvanized spill slope shelves Powder coat finish: 2.4 to 2.5 mills avg
Package Dimensions (HXWXD):	52.00 x 36.00 x 52.00 (1321 mm x 914 mm x 1321 mm)
Spill Containment Sump:	10.44 GAL. (39.55 L)
Net Weight:	N/A
Ship Weight:	371 LBS (168.3 KG)
Number Of Shelves:	None
Shelf Load:	N/A
Cans Per Shelf:	N/A
Spill Containment Sump:	8 GAL. (30 L)

Justrite standard color options:

Yellow	Red	Blue	Green
Silver	Snow White	Light Neutral	Gray

