

PIG® Spill Kit in Bucket

#KIT213 - Absorbs up to 4 gal. • No Wheels • UN1H2/Y30/S



"Grab-and-go" to quickly respond to spills up to 4 gallons. Wall mounting and sign options to maximize visibility.

- Polyethylene bucket with easy-open, screw-on lid can be used to ship or temporarily store used absorbents
- PIG BLUE Socks stop spreading spills; PIG Mat absorbs quickly
- Prepacked container provides easy access to contents
- Large, color-coded label makes identification fast and accurate
- Tamperproof seals help prevent pilfering of spill response supplies
- UN Rating 1H2/Y30/S for Packing Groups II and III
- Use as refill for wall-mount holder (sold separately)
- Only PIG Spill Kits feature PIG Absorbents proven for rapid response
- For information on custom spill kits, just call 1-800-HOT-HOGS (468-4647)

e-mail : info@verisafe.co.th website : www.verisafe.co.th

Tel : 0 2383 9346-7 Fax : 0 2383 9348

VERISAFE



บริษัท เวิร์สแอฟ จำกัด
VERISAFE CO., LTD.

KIT213 Specifications

Fluids Absorbed:	Oils, Coolants, Solvents & Water
Absorbency:	Up to 4 gal.
Spill Volume:	1 - 9 gal.
Lift-out Basket:	No
Outdoor Storage:	No
UN Rated:	Yes
UV Resistant:	No
Wheels:	No
Sold as:	1 each
Weight:	11 lbs.
# per Pallet:	36
Composition:	Bucket - 100% Polyethylene Mat - Polypropylene Socks - Polypropylene & Magnesium Aluminosilicate
Includes:	1 - 10' PIG® BLUE Absorbent Sock (PIG202) 1 - 48" PIG® BLUE Absorbent Sock (4048) 4 - PIG® Universal Mat Pads (MAT203) 6 - Tamperproof Labels (LBL100)

KIT213 Metric Equivalent

Absorbency:	Up to 15.1 L
Weight:	5 kg

Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Certifications, Approvals and Ratings:

UN1H2/Y30/S

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping.

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 122.26 - When applying for a National Pollutant Discharge Elimination System (NPDES) permit, facilities must have a plan in place that describes actions, procedures, control techniques, management practices and equipment available to prevent illegal discharge of pollutants into waterways.

40 CFR 112.7 - SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.

29 CFR 1910.120(j)(1)(vii) - OSHA's HAZWOPER standard requires spill responders to have, "DOT specified salvage drums or containers and suitable quantities of proper absorbents," in areas where spills may occur.

Technical Documents:

(Available at newpig.com)

Product Data Sheet (PDS)

Material Safety Data Sheet (MSDS)

